

PRODUCT INFORMATION

FlameOFF Coatings, Inc Fabric Protector FRX-50

Fabric Protector FRX-50 is a nondurable liquid flame retardant for cotton and paper formulated to both flame retard and resist afterglow on substrate. It is low chalking and does not significantly increase the stiffness.

SPECIFICATIONS:

Appearance:	Clear, slightly amber liquid
pH :	6.0 - 6.7
Solubility:	Completely soluble in water
Specific Gravity:	1.25
Solids:	46% ± 1%
Stability:	Stable for at least one year if stored in a cool, dry location
Water Resistance:	Poor

APPLICATIONS:

Fabric Protector FRX-50 can be applied to either a wet or dry substrate in a pad, sprays, or size press. A dry weight pickup of 10% – 12% is recommended. Recommended drying temperature is 230-250° F.

The data and suggested formulations in this bulletin are based on information believed to be reliable and are offered solely for evaluation, investigation and verification of numerous factors affecting results. FlameOFF Coatings, Inc products are sold with the understanding the purchasers will make their own tests to determine the suitability of these products for the particular use. We assume no liability or responsibility for any damage to person or property resulting from or incident to the use of our products.

Statements concerning the use of FlameOFF Coatings, Inc products are not be construed as recommending the infringement of any patent, and no liability for infringement arising out of any such use is assumed.



FlameOFF Coatings, Inc
9615 Brookhaven Ct
Villa Rica, Georgia 30180

www.flameoffcoatings.com | Phone: 770-241-8145